

Elevate Office Productivity to Achieve Workflow Efficiency

Enhance efficiency in your office with these multi-function laser printers. Equipped with versatile connectivity, the easy-to-navigate customisable short-cut keys and smart solutions such as Application Library help to streamline work processes.

UP TO
40 PAGES/MIN
(A4)
FAST PRINT

QUICK
5.0 s
FIRST PRINT
OUT TIME

UP TO 100 IMAGES/MIN (A4) DUPLEX



UP 10,200
TO 10,200
PAGES
HIGH-YIELD
CARTRIDGE



*Applicable to MF469x and MF465dw



IMPROVE WORK EFFICIENCY / CUSTOMISE WORKFLOWS

The Application Library is packed with innovations to help you work smarter and more efficiently than ever. You can store and print frequently-used forms directly from the device, or distribute your documents electronically to pre-set destinations with just a tap of the button.



INCREASE PRODUCTIVITY

Maximise scanning efficiency with the 50-sheet single-pass Duplex Auto Document Feeder (DADF). Equipped with two Contact Image Sensors (CIS), both sides of the document can be scanned simultaneously in one pass.



MULTIPLE PRINT ENVIRONMENT SUPPORT

In addition to Canon's proprietary UFR II print language, industry standard PCL6 and Adobe® PostScript® 3™ print languages are supported to ensure seamless integration with a wide range of business applications.



ENHANCED DATA PROTECTION

TLS 1.3 encrypts and protects data from sniffing, spoofing and tampering, while the system's integrity can be monitored during startup.

SPE	CIFICATIONS	6	MF469x MF465dw MF461dw		
	Printing Method		Monochrome Laser Beam Printing		
		A4	40 pages/min	36 pages/min	
	Print Speed	Letter	42 pages/min	37 pages/min	
PRINT		2-Sided	33 images/min (A4) / 35 images/min (Letter)	30 images/min (A4) / 31 images/min (Letter)	
	Print Resolution		600 x 600 dpi		
	Print Quality with Image Refinement Technology		1,200 x 1,200 dpi (equivalent)		
	Warm-Up Time (From Power On)		14s		
	First Print Out Time (FPOT)	A4	5 s		
	Recovery Time (From Sleep Mo	ode)	4 s or less		
	Print Language		UFR II, PCL 6, Adobe® PostScript® 3™		
	Auto Duplex Print		Yes		
	Print Margins		Top/Bottom/Left/Right Margin: 5 mm Top/Bottom/Left/Right Margin: 10 mm (Envelope)		
	Supported File Format for USB Direct Print		JPEG, TIFF, PDF		
	Copy Speed	A4	40 pages/min	36 pages/min	
	Copy Resolution	l	600 × 600 dpi	. 5	
	First Copy		000 ·· 300 upi		
COPY	Out Time (FCOT) Platen Glass / ADF	A4	61s		
	Maximum Numl	ber of Copies	Up to 999 Copies		
	Reduce/Enlargement		25 – 400% in 1% increments		
	Copy Features		Collate, 2 on 1, 4 on 1, ID Card Copy, Passport Copy		
	0	Optical	Up to 600 x 600 dpi		
	Scan Resolution	Driver Enhanced	Up to 9,600 x 9,600 dpi		
	Scan Type		Colour Contact Image Sensor		
	Maximum	Platen Glass	Up to 216 x 297 mm		
	Scan Size	ADF	Up to 216 x 356 mm		
		Platen Glass	1.9 s or less		
SCAN	Scan Speed*1	ADF	1-Sided: 50 images/min (mono), 40 images/min (colour) 2-Sided: 100 images/min (mono), 80 images/min (colour)		
	Colour Depth		24-bit		
	Pull Scan		Yes, USB and Network	(
	Push Scan (Scan To PC) with MF Scan Utility		Yes, USB and Network		
	Scan To Cloud		MF Scan Utility		
	Scan Driver Compatibility		TWAIN, WIA		
	SEND Method		SMB, Email, FTP, iFAX Simple	SMB, Email, FTP	
₽	Colour Mode		Full Colour, Greyscale, Mono	chrome	
SEND	Scan Resolution		300 x 600 dpi		
	File Format		JPEG, TIFF, PDF, Compact PDF, PDF (OCR)		
	Modem Speed		Up to 33.6 Kbps (Up to 3 sec/page)	-	
	Fax Resolution		Up to 200 x 400 dpi	-	
	Compression Method		MH, MR, MMR, JBIG	-	
	Memory Capacity*2		Up to 256 pages	-	
	Speed Dials		Up to 104 dials	-	
	Group Dials / Destinations		Max. 103 dials / Max. 50 destinations in one group	-	
FAX	Sequential Broadcast		Max. 114 destinations —		
	Receive Mode		Fax Only, Fax/Tel Auto Switch,	-	
			Answer Mode, Manual Permanent Fax Memory Backup -		
	Memory Backup Fax Features		Fax Forwarding, Remote Reception, PC Fax (Transmit Only), DRPD, ECM, Auto Redial, Fax Activity Reports,		
			Fax Activity Result Reports, Fax Activity Management Reports		

				MF469x	MF465dw	MF461dw	
PAPER HANDLING	Input Tray Capacity (Plain Paper, 80 g/m²)	Þ	Cassette		250 sheets		
		Standard	Manual Feed Tray	100 sheets			
		ş	ADF	50 sheets Duplex, Single Pass			
		Optional	Paper Feeder	550 sheets			
		Maximum		900 sheets (Standard + 1 Paper Feeder)			
	Output Tray Capacity (Plain Paper, 80 g/m²)		150 sheets				
			per Tray	A4, A5, A6, B5, Legal, Letter, Executive, Statement, Foolscap, Government Letter, Government Legal, Indian Legal, Index Card, Postcard, Envelope (COM10, Monarch, DL, C5), Custom (min. 76 x 127 mm to max. 216 x 356 mm)			
	Media Size	ADF		A4, B5, A5, B6, Letter, Legal			
		2-Sided		(min. 148 x 105 mm to max. 216 x 356 mm)			
			nting	A4, Legal, Letter, Foolscap, Indian Legal, Custom (min. 210 x 279 mm to max. 216 x 356 mm)			
	Media Type		Plain Paper, Recycled Paper, Label, Postcard, Envelope				
	Media Weight		per Tray	60 – 163 g/m²			
		AD		50 – 105 g/m²			
	Standard	Wir		USB 2.0, 10Base-T/100Base-TX/1000Base-T		UUUBASE-I	
	Interface	Wir	eless	Wi-Fi 802.11b/g/n (Infrastructure Mode, WPS, Direct Connection)			
		Print		LPD, RAW, WSD-Print (IPv4, IPv6)			
	Network Protocol	Sca	an	Email, SMB, WSD-Scan (IPv4, IPv6), FTP			
CONNECTIVITY & SOFTWARE		TCP/IP Application Services		Bonjour(mDNS), DHCP, BOOTP, RARP, Auto IP (IPv4), DHCPv6 (IPv6)			
		Ма	nagement	SNMP v1/v3 (IPv4, IPv6), HTTP/HTTPS, SNTP			
		Wired		IP/Mac Address Filtering, HTTPS, SNMPv3, IEEE8021X, IPsec, TLS 1.3			
	Network Security	Wir	eless	V WPA-E	de: WEP (64/128 bit), WPA-PSK (TKIP/AES), WPA2-PSK (TKIP/AES), -EAP (AES), WPA2-EAP (AES), ss Point Mode: WPA2-PSK (AES)		
	Mobile/Cloud Printing Solutions		Canon PRINT Business app, Canon Print Service (Android), AirPrint, Mopria, Microsoft Universal Print				
	Compatible Operating Systems*3		Windows 10/11, Windows Server 2012/2012 R2/ 2016/2019/2022, macOS 10.13 or later, Linux, Chrome OS				
	Other Features		Department ID, Secure Print, Skip Blank Page, Application Library				
	Software Included		Printer Driver, Fax Dr MF Scan Utility		Printer Driver, Scanner Driver, MF Scan Utility, Toner Status		
	Device Memory		1GB				
	Display		127mm (5") LCD Touchscreen with vari-angle				
	Power Requirements		AC 220 – 240 V, 50/60 Hz				
	Power Consumption	Op	eration	480 W (max. 1,280 W)			
		\vdash	ndby	8 W			
GENERAL		Sle		0.9 W			
	Operating Environment	-	nperature	10 – 30°C			
	Environment Humidity		20 – 80% RH (no condensation)				
	Monthly Duty Cycle'4 Dimensions (W x D x H)		80,000 pages 420 x 460 x 375 mm				
	Weight'5		420 x 460 x 5/5 Hilli 15.6 kg				
	Toner	Sta	ndard	Cartridge 070: 3,000 pages (Bundled: 3,000 pages)			
	Cartridge'6	Hig		Cartridge 070H:10,200 pages			
MAL	Paper Feeder		Cassette Feeding Unit-AH1 (550 sheets)				
OPTIONAL	Barcode Printing		Barcode Printing Kit-E1E				
1 Scan resolution 300 x 300 dpi.							

- *1 Scan resolution 300 x 300 dpi.
- Scan resolution 300 x 300 dpi.
 Based on ITU-T #1 Chart (standard mode).
 The latest drivers for Windows, Windows Server, Mac OS and Linux can be downloaded from https://asia.canon/en/support website when available.
 Monthly Duty Cycle value provides a means of comparison for product robustness in relation to other Canon laser printer devices, and does not refer to actual maximum image output per month.

- Excluding toner cartridge.
 Toner cartridge yield is in accordance with ISO/IEC 19752.



CANON INDIA PVT. LTD.

7th Floor, Tower B, Building #5, DLF Epitome Building, DLF Phase III, Gurugram-122002 Ph.: 0124-4160000 | Fax: 0124-4160011 | Web: in.canon Delighting You Always

DEALER'S STAMP

This document is for information purpose only. The contents are subject to change without notice. Product options, name and availability may vary by regions. We expressly disclaim any liability or contractual obligations with respect to this document. Brands and product names are trademarks and/or registered trademarks of their respective owners.