




## Refillable Ink Tank Printer with LCD Screen for Low-Cost Printing



This high-performance all-in-one printer combines low-cost printing with a backlit LCD screen for easy operation.

### EASY, HASSLE-FREE INK REFILL

Ink refilling is now made easy. Each ink bottle nozzle is designed to fit seamlessly only into the designated ink tank, eliminating potential mixing accidents.



### EASY MAINTENANCE

The easy-to-replace maintenance cartridge makes maintenance fuss-free and extends the printer's lifespan even when printing in high volumes.



### 3CM SEGMENT LCD PANEL

Easily navigate and configure printer settings using the LCD screen, which displays information at a glance.



## SPECIFICATIONS / PIXMA G2770

PRINT	Maximum Printing Resolution		4800 (horizontal) <sup>1</sup> x 1,200 (vertical) dpi	
	Print Speed <sup>2</sup>		11 / 6 images per minute	
	Photo (4 x 6")		9 / 14 s	
SCAN <sup>3</sup>	Scanner Type		Flatbed	
	Scanning Method		Contact Image Sensor (CIS)	
	Optical Resolution <sup>4</sup>		600 x 1,200 dpi	
COPY	Maximum Document Size		A4, LTR (216 x 297 mm)	
	Copy Speed <sup>5</sup>	Colour	23 s	
		sFCOT/Simplex	3.2 images per minute	
PAPER HANDLING	Maximum Copies		99 prints	
	Maximum Document Size		A4, LTR	
	Maximum Input Capacity	Plain Paper (64 g/m <sup>2</sup> )	Up to 100 sheets	
		Photo Paper (4 x 6")	Up to 20 sheets	
SYSTEM REQUIREMENTS & GENERAL SPECIFICATIONS	Media Size		A4, A5, A6, B5, LTR, LGL, Executive, Legal, Foolscap, F4, Oficio2, B-Oficio, M-Oficio, Envelope (COM10, DL, C5, Monarch), Card Size (91 x 55 mm), 4 x 6", 5 x 7", 7 x 10", 8 x 10", Square (89 x 89 mm, 127 mm x 127 mm), Custom (width: 55 – 216 mm, length: 89 – 1,200 mm)	
	Media Type		Plain Paper (64 – 105 g/m <sup>2</sup> ) High Resolution Paper (HR-101N) Photo Paper Plus Glossy II (PP-201, PP-208) Glossy Photo Paper (GP-508) Photo Paper Plus Semi-Gloss (SG-201) Photo Paper Pro Luster (LU-101) Matte Photo Paper (MP-101) Double-Sided Matte Paper (MP-101D) Photo Stickers (PS-208, PS-808) Envelope	
	Operating System Compatibility	Please visit <a href="https://asia.canon">https://asia.canon</a> to confirm OS compatibility and to download the latest drivers.	Windows 11 / 10 / 8.1 / 7 SP1 <sup>6</sup> macOS 10.14.16 – 12 or later Chrome OS	
CONSUMABLES	Interface		USB 2.0	
	Canon Printing Apps		Easy PhotoPrint Editor, Creative Park, Easy Layout Editor, PosterArtist Lite, PosterArtist (Web), Canon Inkjet Smart Connect	
	Power		AC 100 – 240 V, 50/60 Hz	
Power Consumption <sup>7</sup>		14 W (Standby: 0.6 W)		
Duty Cycle		Up to 3,000 Prints/month		
Recommended Monthly Print Volume		150 – 1,500 Prints		
Dimensions (W x D x H)	Operation Panel	Display	1.2" / 3.0 cm Segment LCD (Monochrome)	
	Factory Configuration		416 x 337 x 177 mm	
	Output/Trays Extended		416 x 557 x 268 mm	
Weight		6.0 kg		
Ink Bottles	Type/Colours		Pigment Ink / Black Dye-Based Ink / Cyan, Magenta, Yellow	
	Print Yield <sup>8</sup> (A4, Prints)		GI-71 PGBK: 6,000 (Standard) / 7,600 (Economy) <sup>10</sup> GI-71 C, M, Y: 7,700 <sup>9</sup> (Standard) / 8,100 <sup>9</sup> (Economy) <sup>10</sup>	
User Replaceable Maintenance Cartridge		MC-G04		

### Specifications are subject to change without notice.

<sup>1</sup> Ink droplets can be placed with a pitch of '0.000529 cm (1/4800 inch)' at minimum.

<sup>2</sup> Document print speeds are the averages of ESAT (Word, Excel, PDF) in Office Category Test for the default simplex mode, ISO/IEC 24734. Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host computer.

Print speed may vary depending on system configuration, interface, software, document complexity, print mode, Print coverage, type of paper used etc.

<sup>3</sup> TWAIN driver (ScanGear) is based on the TWAIN specification V1.9 and requires the Data Source Manager comes with the operating system.

<sup>4</sup> Optical resolution is a measure of maximum hardware sampling resolution, based on ISO 14473 standard. Optical resolution scan is available, only when you use TWAIN Driver.

<sup>5</sup> Copy speeds are the average of sFCOT and sESAT, ISO/IEC 29183. Copy speeds (ADF) are ESAT of copy in sequence, ISO/IEC24735. Copy speed may vary depending on document complexity, copy mode, Print coverage, type of paper used etc. and does not take into account warm up time.

<sup>6</sup> Operation can only be guaranteed on a PC with a pre-installed Windows 7 or later.

<sup>7</sup> When copying ISO/JIS-SCID N2 (printed by inkjet printer) on A4 size plain paper using default settings.

<sup>8</sup> The Print yield (A4 size) is based on the consumption data from the succeeding ink bottle but not the first ink bottle. Print yield is the estimated value based on Canon individual test method using the ISO/IEC 24712 chart under ideal print conditions & continuous printing simulation with the replacement after initial setup. Mentioned print yield is from the replacement set of 4-ink bottles (C/M/Y/BK). Black bottle contains 135ml ink and each colour bottle contains 70ml of ink. Print yield varies significantly depending on contents printed and other factors.

<sup>9</sup> Based on 1 set of colour bottles.

<sup>10</sup> The Economy mode reduces the ink consumption by lowering the density. More Print can be printed than the standard mode.



## CANON INDIA PVT. LTD.

Corporate Office: 7<sup>th</sup> Floor, Tower B, Building #5, DLF Epitome Building, DLF Phase III, Gurugram-122002

Ph.: 0124-4160000 | Fax: 0124-4160011 | Web: [in.canon](http://in.canon)

### DEALER'S STAMP

This document is for information purpose only. The contents are subject to change without notice. Product options, name and availability may vary by regions. We expressly disclaim any liability or contractual obligations with respect to this document. Brands and product names are trademarks and/or registered trademarks of their respective owners.