



MOBILE POS



M10 SE | SPECIFICATIONS

Processor	A53 Quad-core, up to 2.0GHz	Positioning	AGPS, GPS, Glonass, Beidou, Galileo
OS	Android 13	Camera	Front camera: 0.3M pixels fixed focus camera Rear camera: 5M pixels, autofocus and flashlight
Memory	2GB+16GB Micro SD Card (Up to 2TB)	NFC	Android NFC, ISO / IEC 14443, MIFARE, support Type A/B
Display & Touchscreen	5", 480×854 Capacitive multi-touch	SIM	2*SIM 1*SIM+1*eSIM (Optional)
Scanner	· Optional 1 : NONE · Optional 2 : LANDI Scanner module	Connection	1 USB-Type C 2.0 2 Pin POGO
Buttons	1 Power key (Right Side) 2 scan code keys are located on each side	Battery	Main Battery: 3.7V/3000mAh, Removable
Audio	Speaker: 2W 95dB@0.1m MIC: Single-MIC Headset: USB Type-C	Power Supply	5V / 2A
Connectivity	Cellular: 4G fallback 3G and GPRS, Global band Wi-Fi: IEEE 802.11 a/b/g/n/ac 2.4G and 5G Bluetooth: Bluetooth 5.0,support BLE	Accessories (Optional)	·1+1 Charging Dock · Wrist Strap · Screen Protector · Protective Casing
Protection	IP65 1.2m drop tested *Data from LANDI lab	Environment	Operating temperature: -10 ℃ to +50 ℃ Storage temperature: -20 ℃ to +55 ℃ Operating humidity: 10% to 90% non-con- densing
Certification	CE, CB, FCC, IC, RoHS, WEEE		

