



SRP - S300 TOEK

Linerless printer

- Fashion appearance
- With high speed, excellent stability and durability
- Paper detection by transmission type, accurately and rapidly
- Imported thermal printer head, printing clearly and stable
- With function for automatic correction paper and carbon

Specification

SRP - S300 TOEK

Print Characteristics	
Print Method	Direct Thermal
Print Speed	Up to 170 mm/sec
Print Resolution	203 dpi
Print Width	Up to 72 mm
Sensor	Paper End,Black mark, Cover Open, Paper taken (option)
Media Characteristics	
Media Type	Linerless Restick
Media Width	80 mm optional (40/58/62/83)mm
Media Roll Diameter	Up to 103 mm
Media Thickness	0.06 ~ 0.09 mm
Supply Method	Easy Paper Loading
Physical Characteristics	
Dimensions (W x D x H)	156 x 210x 160 mm (6.14 x 8.27 x 6.30 inch)
Weight	2.00 kg (4.40 lbs.)
Electrical	EnergyStar Certified, External supply housed Internally (Adapter 24V /2.5 A)
Drawer Port	2 ports (Via y-type adaptor)
Performance Characteristics	
Memory	128 Mb SDRAM, 256 Mb Flash optional(256 Mb SDRAM, 512 Mb Flash)
NV Image Memory	256 Kbytes (Mono)
Receive Buffer	4 Kbytes
User Define Buffer	12 Kbytes
Interface	Standard: USB V2.0 FS + Ethernet

Certifications



WPC



POSIFLEX TECHNOLOGY (INDIA) PVT. LTD.

#7/3, 3rd Floor, Jeet Dynasty, Swamy Vivekananda Rd, Nagavarapalya, Bengaluru, Karnataka 560093
 Tel : +91 80 4078 2700 | Mob : +91 9535432110
 Email : marketing@posiflexindia.com | www.rugtek.com

Authorized Distributor / Reseller

Specification

SRP - S300 TOEK

Environment Characteristics	
Temperature	Operating: 0 ~ 40 °C (32 ~ 104 °F) Storage: -20 ~ 60 °C (-4 ~ 140 °F)
Humidity	Operating: 10 ~ 80 % RH Storage: 10 ~ 90 % RH
Seling	IP21
Software	
Emulation	BXL / POS,SLCS,BPL-Z,BPL-C
Driver / Utility	Windows Driver OPOS/JPOS Driver Linux/Mac CUPS Driver Virtual COM USB/Ethernet Driver Utility Program Network Auto Installer
SDK / Plugin	Android/iOS/Windows SDK Linux SDK Xamarin SDK Web Print SDK Cordova Plugin
Application	mPrint App (Android, iOS)
MDM (Optional)	BIXOLON Profile Manager - XPM™, XCM™ (Windows, Android)
Fonts / Graphics / Symbolologies	
Character Size	Font A: 12 x 24, Font B: 9 x 17, Font C: 9 x 24, KOR, CHN, JPN: 24 x 24 Characters Per Line SRP-350plusV: Font A: 42, Font B, C: 56, KOR, CHN, JPN: 21 SRP-352plusV: Font A: 48 Font B, C: 64 KOR, CHN, JPN: 24
Character Sets	Alphanumeric: 95 Extended Graphics: 128 x 35 page International: 32
Graphics	Supporting user-defined fonts, graphics, formats, and logos
Barcode Symbolologies	1D: Coda Bar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E 2D: Data Matrix, PDF417, QR code
Accessories	
Standard	Power Card, USB A-B Cable 1.8 m
Optional	Wall mount, External buzzer

Certifications



POSIFLEX TECHNOLOGY (INDIA) PVT. LTD.

#7/3, 3rd Floor, Jeet Dynasty, Swamy Vivekananda Rd, Nagavarapalya, Bengaluru, Karnataka 560093
Tel : +91 80 4078 2700 | Mob : +91 9535432110
Email : marketing@posiflexindia.com | www.rugtek.com

Authorized Distributor / Reseller