

POSIFLEX

Lighten the Atmosphere



AURA PP-7900

3" Thermal Receipt Printer

AURA PP-7900

Specification	AURA PP-7900
Function	3" Thermal Printer with auto cutter
Max. Print Speed	Up to 250 mm/sec
Resolution	576 dots/line (W 8 dots/mm x H 8 dots/mm)
Paper Width	80 mm or 58 mm
Printing Width	64 mm [512 dots/line, default] / 72 mm [576 dots/line] / 54 mm [424 dots/line]
Input Buffer	6KB
LED Indicator	Power; Error; Paper out
Cutter	Auto cutter
Sensor	Cover Open + Out-of-paper ; Paper near end
Power Supply	24V/60W
Interface	USB (True USB/Virtual COM selectable) + Serial + LAN
Dimension (W x D x H in mm)	127 x 127 x 127
Weight (N. W. in kg)	0.9
Surface Finish	Texture

Language Support	
International Character Set	15 international character sets (Denmark I, Denmark II, Ex-Yugoslavia, France, Germany, Italy, Japan, Korea, Latin America, Norway, Spain, Spain II, Sweden, UK, USA)
Character Code Page	23 code pages supported
Bar Code Printing	UPC-A/E, EAN13/8, ITF, CODE39/93/128, CODABAR, QR Code, PDF417
Unicode	Yes

Options	
Options	Kitchen Bell Function

*Designed and Manufactured in Taiwan by Posiflex Technology, Inc.

*The product information and specifications are subject to change without prior notice.

Certifications	      	EN20240506V4
----------------	--	--------------

POSIFLEX

POSIFLEX TECHNOLOGY, INC.

No. 23, Datong St., Tucheng Dist., New Taipei City 23679, Taiwan
Tel : +886-2-2268-5577 E-mail : sales@posiflex.com.tw
Fax : +886-2-2268-5388 www.posiflex.com

Authorized Distributor / Reseller