

C20 SE

| SPECIFICATIONS



Android ECR

Processor	Quad-core, 2.0GHz	Weight	Single-display : Net weight 3.9 kg, Gross weight 5.7 kg Dual-display: Net weight 4.5 kg, Gross weight 6.4 kg
OS	Android 13	Audio	Speaker:5W,100dB@1m, Dual Speaker MIC: Dual Microphone Headset: 3.5mm audio jack
Memory	Internal: 4GB RAM+32GB FLASH External: Micro SD Card (Up to 2TB)	Connectivity	Wi-Fi: IEEE802.11 a/b/g/n/ac/ax 2.4G and 5G ETH:1000M Bluetooth 5.0, support BLE
Main Display	15.6",1920x1080,FHD capacitive multi-touch	NFC (Optional)	Android NFC SO/IEC14443、1S015693 compliant supportType A/B, Mifare, Felica (Only supported on the 10.1"Premium CFD)
Customer Display	Optional 1:None Optional 2: 10.1" Standard CFD (1280x800 display only) Optional 3:10.1"Premium CFD (1280x800,Touch panel, QR Camera, NFC)	Camera	Optional 1: NONE Optional 2: 0.3M pixels, QR code scan (Only supported on the 10.1"Premium CFD)
Ports	1 USB Typec-C debug port, 1 Power port, 4*USB Type-A 2.0, 1 USB Type-A 3.0, 1*RJ22 Serial Port 1 Micro SD slot, 1*RJ45 Ethernet port 1 RJ11 Cash drawer port 1 3.5mm Audio jack	Power Supply	19V/3.42A
Buttons	1 Power key with indicator light 2 Volume keys	Environment	Operating temperature : 0°C to +40°C Storage temperature : -20°C to +60°C Operating humidity: 10% to 90% non-condensing
Size	400mm (L) x 284mm (W) x 402mm (H) 15.75" x 11.18" x 15.83"	Certification	CE/CB/FCC/IC/WEEE/RoHS



Optional 2nd Screen



Optional 2nd Screen

C20 Lite

| SPECIFICATIONS

Processor	Quad-core,2.0GHz	Buttons	Power button
OS	Android 13	communication	ETH 100M, Wi-Fi: IEEE802.11 b/g/n 2.4G, Bluetooth 4.2, support BLE
Memory	2GB RAM+16GB FLASH 4GB RAM+32GB FLASH (Optional) Micro SD Card (Up to 2TB)	Audio	Speaker: 3Wspeaker,90dB@1m Headset: 3.5mm audio jack
Main Display	15.6",1366x768,HD 15.6",1920x1080,FHD (Optional) capacitive multi-touch	Power Supply	19V/2.1A
Customer Display	Optional 1: None Optional 2:10.1"at 1280x800 HD	Size	L- 20cm W-38cm H-33.5cm 7.87" x 14.96" x 13.19"
Ports	1 Micro USB,debug port 4 USB Type-A 2.0 1 RJ22 Serial port, 1 MicroSD slot, 1 Power port, 1 RJ45 Ethernet port, 1 RJ11 Cash drawer port, 1 3.5mm Audio port	Environment	Operating temperature: 0°C to +40°C Storage temperature : -20°C to +60°C Operating humidity: 10% to 90% non-condensing
		Certification	CE/CB/FCC/IC/WEEE/RoHS