LP-46 Plus

Desktop BarCode Printer

SUPERIOR, FAST, AFFORDABLE PERFORMANCE

- USB, ETHERNET & SERIAL
- FAST SPEED PRINTING
- USER FRIENDLY DESIGN
- POWER SAVING
- CLEAR PRINTING QUALITY

Specification

Printing Method	Thermal Line Printing - Direct Thermal & Thermal Transfer
Resolution	8 dots/mm (203 dpi)
Max. print speed	152.4 mm (6")/second
Max. print width	108 mm (4.25")
Max. print length	2,794 mm (110")
Enclosure	ABS plastic
Physical dimension	204 mm (W) x 164 mm (H) x 280 mm (D) 8.03“ (W) x 6.46“ (H) x 11.02“ (D)
Weight	2.4 kg
Label roll capacity	127 mm (5“) OD
Ribbon	300 m long, max. OD 67 mm, 1” core (ink coated outside) 110 m long, max. OD 40 mm, 0.5” core (ink coated outside)
Ribbon width	40 mm ~ 110 mm (1.6” ~ 4.3”)
Processor	32-bit RISC CPU
Memory	128 MB Flash memory ; 64 MB SDRAM
Interface	USB 2.0, Ethernet & Serial Interface
Power	Input: AC 100-240V, 2.5A, 50-60Hz ; Output: DC 24V, 2.5A, 60W
Switch / Button	1 power switch, 1 feed and pause button & 1 LED
Sensors	Transmissive gap sensor Black mark reflective sensor (position adjustable) Ribbon end sensor ; Head open sensor
Internal fonts	8 alpha-numeric bitmap fonts
Bar code	1D bar code, Code 128UCC, Code 128 subsets A, B, C, - EAN128, Interleaved 2 of 5, Interleaved 2 of 5 with check digit, Code 39, Code 39 with check digit, Code 93, EAN13, EAN8, UPCA, UPCE, EAN and UPC 2 (5) digits add-on, etc.. 2D bar code, GS1 DataBar, GS1 DataMatrix, Maxicode etc.
Font/barcode rotation	0, 90, 180, 270 degree
Printer language	TSPL-EZD (Compatible to EPL, ZPL, ZPL II, DPL)
Media type	Continuous, die-cut, black mark, fan-fold, notched
Media width	20 ~ 112 mm (0.8“ ~ 4.4“)
Media thickness	0.06 ~ 0.19 mm (2.36 ~ 7.48 mil)
Media core diameter	25.4 ~ 38 mm (1” ~ 1.5”)
Environment condition	Operation: 5 ~ 40°C, 25 ~ 85% non-condensing Storage: -40 ~ 60°C, 10 ~ 90% non-condensing
Dealer Option	Peel-off Module, • Guillotine cutter (full cut and partial cut) 1
Warranty	Year Onsite

ENERGY STAR

USER FRIENDLY DESIGN

- Superfast 6ips Speed
- Memory: 128 MB Flash, 64 MB SDRAM
- Interface: USB 2.0, Ethernet & Serial Interface
- Print Head Life : 25 km

ONSITE WARRANTY* 1 YEAR INCLUDING PRINTHEAD

* BUY * 1 YEAR EXTENDED WARRANTY Avail within 90 days of purchase

Segments

Healthcare | Supermarkets | Warehouses | Jewellery Shops | Textile Shops | Logistics | Toll Plazas

ORDERING INFORMATION

SKU No	SKU Title
3006210043	LP-46 PLUS

© Copyright 2007. TVS Electronics Ltd. All rights reserved. All brand and product names are trademarks or registered trademarks of the respective holders and are hereby recognised as such. All product specifications are subject to change without prior notice.

TVS ELECTRONICS LIMITED

www.tvs-e.in

For Sales Enquiry
044 6688 8822
sales-support@tvs-e.in

For Service Enquiry
1860 425 2078
support@tvs-e.in